



Assembly Instructions

Model:	Jeep JL (Wrangler) & JT (Gladiator)
Description:	Rear Speaker Kit
Part Number:	JC1-169SB
Assembly Time:	120 Minutes (2 Hours)

Before you begin, read through these instructions and check that all parts are present. Please note that MB Quart cannot assume any responsibility for damage resulting from incorrect installation.

Parts List		
No.	Component Name	Qty
1	6x9 Coaxial Speakers	2
2	Speaker Bracket	2
3	Harness Adapter	2

Tools Required	
1	M4 Allen Bit
2	T20 & T30 Torx Bit
3	Rotary Cutting Tool (i.e. Dremel)
4	Painters Tape
5	Marker

Parts Photo



Rear Speaker Installation

- Remove four 5mm Allen bolts to remove the OEM Grill



- Remove and disconnect (4) T30 Torx screws from the port and (5) T20 Torx screws from both speakers



- Apply painter tape to the soundbar, then hold the 6x9 speaker mounting plate up and mark the speaker opening



Rear Speaker Installation

- Remove 6x9 mounting plate to show roughly the cutting and using a rotary cutting tool, cut a hole similar to the picture on the right

BE VERY CAREFUL not to cut the OEM wiring as this will be used with the 6x9 speaker



- Mount the 6x9 metal plate to the soundbar with (8) Phillips screws



Rear Speaker Installation

- Connect the harness adapter to the OEM plug and connect to the 6x9, then mount the 6x9 to the mounting plate using (4) M4 Screws and washers



- Mount the new soundbar grill for the 6x9 with the OEM 5mm bolts



FCC Notification

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a mobile installation. This equipment generates uses and can radiate radio frequency energy. If not installed and used in accordance with the instructions, this equipment may cause harmful interference to radio communications. There is no guarantee that interference will not occur in a particular installation.

WARNING: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment complied with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20cm between the radiator and your body.